



Direct suspended luminaire, equipped with LED technology. Optionally available with indirect light.

Housing is made of aluminium, powder coated according to RAL colour chart.

Light is distributed via an opal acrylic diffusor, optionally via a microprismatic cover for offices (UGR<19).

According to customer requirements, light strips or light figures are possible on request.

Delivery inclusive suspension accessories.

Type	Lumen	System Power	Dimension (l x w x h)
PL 3 - 853 opal	3.100 Lumen	23 Watt	853 x 61 x 83 mm
PL 3 - 1133 opal	4.100 Lumen	32 Watt	1.133 x 61 x 83 mm
PL 3 - 1413 opal	5.000 Lumen	40 Watt	1.413 x 61 x 83 mm
PL 3 - 1693 opal	6.150 Lumen	48 Watt	1.693 x 61 x 83 mm
PL 3 - 853 opal HE	1.800 Lumen	14 Watt	853 x 61 x 83 mm
PL 3 - 1133 opal HE	2.300 Lumen	18 Watt	1.133 x 61 x 83 mm
PL 3 - 1413 opal HE	3.050 Lumen	23 Watt	1.413 x 61 x 83 mm
PL 3 - 1693 opal HE	3.550 Lumen	26 Watt	1.693 x 61 x 83 mm

Technical Information:

Voltage:	220-240 V / 50-60 Hz
Protection Class:	1
Protection Type:	IP 20
Ballast:	switchable
Cover:	opal
Colour:	RAL colour chart
Light Colour:	4.000K
CRI:	RA>80

Options:

- Light Colour 3.000K
- Direct and indirect light
- Dimmable DALI
- Microprismatic cover UGR < 19 (e.g. type PL 3 mprm)
- Version Wallwasher

Dimension Drawing:

