



T0 Typ D/F

Recessed door

datasheet.headline.einsatzgebiete.title

Public Areas: Entrance Areas, Escape Routes

Public Institutions: Court Houses, Government Buildings

Healthcare: Laboratories and Research Facilities, Clean rooms (pharmacy and medical technology), Pharmacies (Production)

Hotels and Gastronomy: Hotels and Resorts

Industry: Laboratories and Research Facilities, Clean rooms (electronics and semiconductor technology)

Businesses, Recreation and Culture: Stadiums



datasheet.headline.technischeAnforderungen.title

Design: Wood, Varnish, Laminate

Acoustics: Airborne Sound Reduction

Hygiene: Cleanable by vacuuming, Wipeable, Antibacterially disinfectable, Virucide disinfectable

Dimensions

Width	625 - 3 000 mm
Height	1 750 - 3 000 mm
Height incl. Top panel	4 000 mm

Technical Details

Climate class	DIN EN 12219	2, 3
mechanischeBeanspruchung_Wert	group E	
Installation options	Drywall, Solid walls	
Edge design (door leaf)	Solid wood edge band, Solid wood inset edge band, RAL-/NCS coated edge	
Frame type	Solid wooden frame	
Number of leaves	double-leaf	

Acoustics

objectbrick.Akustik.Bauakustik.title

Weighted sound reduction index	DIN EN ISO 10140-2	R _w	37	dB
--------------------------------	--------------------	----------------	----	----



Durability

Suitable for use in moisture-room	moisture resistant
Suitable for use in wet-room	capable for wet rooms

Surfaces

Surfaces	real wood veneer, , ,
----------	-----------------------

Sustainability

Indicators

Emission of formaldehyde	< 3 µg/m ³
--------------------------	-----------------------

Evidence of emission measurements

Indoor Air Comfort	Fulfills
Indoor Air Comfort Gold	Fulfills
AgBB	Fulfills
BREEAM International	Conform
LEED v4	Conform
DGNB	Conform

deklarationen_und_nachweise

Emission

Sustainable