



RIBline Timber Slats Ceiling

Cladding system

datasheet.headline.einsatzgebiete.title

Businesses, Recreation and Culture: Banks, Shopping Centres, Cinemas and Theatres, Concert Halls, Museums, Public Swimming Pools, Gymnasiums, Stadiums, Sales Areas, Places of Assembly

Education: Library Rooms, Research Rooms, School of Higher Education, Schools, Teaching, Class and Educational Rooms

Work: Common Rooms, Facilities for Meetings, Conventions and Conferences, Stage and Studio Rooms, Office buildings, Film- & Recording Studios, Data Centres, Broadcasting Rooms, Television Studios, Utility Rooms, Assembly Rooms, Administration Buildings

Healthcare: Pharmacies (Production), Clinics and Hospitals, Laboratories and Research Facilities, Operating Theatres, Clean rooms (pharmacy and medical technology)

Transport: Airports, Train Stations

Hotels and Gastronomy: Restaurants and Canteens, Commercial Kitchens, Hotels and Resorts

Technical Details

Material: Gypsum core with Wood veneer surface;

System weight: Approx. 2-3 kg/m of lamella depending on the Geometry (Excluding Substructure)

Mounting and Demounting: Hook-in and Slide options.

Geometry of Solo Lamella:

Thickness: 22 mm, 38 mm

Width: 22 mm, 38 mm, 54 mm, 65 mm, 70 mm

Length: 500 - 2,500 mm

Dimensions

Length	600 - 1 200 mm
Width	300 - 600 mm



Thickness of Lamella: 18 mm, 22 mm, 38 mm
Width of Lamella: 38 - 65 mm

Fire protection

objectbrick.Brandschutz.Baustoffklasse.title

Building material class	DIN EN 13501-1	B - s1,d0
-------------------------	----------------	-----------

Durability

Stress class	DIN EN 13964	A
--------------	--------------	---

Surfaces

Real wood Veneer, Engineered Wood Veneer (For all the veneers, please refer pg 08 on Brochure)

Sustainability

Evidence of emission measurements

CO2 Einsparung	%
CO2 Bilanz	kg/m ²
Gaseinsparung	%
Wassereinsparung	%