



ic audio DL EN54

ELA Loudspeaker for Voice Alarm

Depending on the requirements, different versions of loudspeakers for necessary corridors are available - for example ELA loudspeakers acc. to EN54 with certified voice alarm in case of fire.

- ELA loudspeakers acc. to EN54 with protective box for voice alarm

Technical Details

ic audio DL 06-130/T-EN54

min. ceiling element width: 356 mm
installation depth: 103 mm
diameter: 180 mm
height: 106 mm
weight: 1.30 kg
protective box: required
power rating: 6/3/1.5 watt
connector: 2-pole ceramic clamp

ic audio DL 20-130/T-EN54

min. ceiling element width: 356 mm
installation depth: 129 mm
diameter: 180 mm
height: 132 mm
weight: 1.70 kg
protective box: required
power rating: 20/15/10/5 watt
connector: 2-pole ceramic clamp

ic audio DL 06-165/T-EN54

min. ceiling element width: 383 mm
installation depth: 109 mm
diameter: 220 mm
height: 112 mm
weight: 1.30 kg
protective box: required
power rating: 6/3/1.5 watt
connector: 2-pole ceramic clamp

ic audio DL 10-165/T-EN54

min. ceiling element width: 383 mm
installation depth: 109 mm
diameter: 220 mm
height: 112 mm
weight: 1.49 kg
protective box: required
power rating: 10/6/3/1.5 watt
connector: 2-pole ceramic clamp



ic audio DL 06-200/T-EN54

min. ceiling element width: 419 mm
installation depth: 134 mm
diameter: 267 mm
height: 137 mm
weight: 2.05 kg
protective box: required
power rating: 6/3/1.5 watt
connector: 2-pole ceramic clamp

ic audio DL 10-200/T-EN54

min. ceiling element width: 419 mm
installation depth: 135 mm
diameter: 268 mm
height: 138 mm
weight: 2.98 kg
protective box: required
power rating: 10/6/3/1.5 watt
connector: 2-pole ceramic clamp

ic audio DL 20-200/T-EN54

min. ceiling element width: 419 mm
installation depth: 191 mm
diameter: 267 mm
height: 194 mm
weight: 3.43 kg
protective box: required
power rating: 20/15/10/5 watt
connector: 2-pole ceramic clamp