



## SK30

### Protective Box for Built-In Part Round/Square

Besides adapted additional equipment, external fixtures can also be integrated into LMD fire rated metal ceilings. The installation of protective boxes is necessary to maintain the fire resistance class.

- integration of external fixtures possible
- protective boxes required to maintain the fire resistance class

#### Technical Details

---

##### SK30/18-L

shape of protective box: oblong  
thickness of protective box: 18 mm  
length of protective box, external dimension: 1,726 mm  
length of protective box, internal dimension: 1,651 mm  
width of protective box, external dimension: 385 mm  
width of protective box, internal dimension: 306 mm  
height of protective box, external dimension: 125 mm  
height of protective box, internal dimension: 107 mm

##### SK30/25-L

shape of protective box: oblong  
thickness of protective box: 25 mm  
length of protective box, external dimension: 1,726 mm  
length of protective box, internal dimension: 1,637 mm  
width of protective box, external dimension: 385 mm  
width of protective box, internal dimension: 292 mm  
height of protective box, external dimension: 125 mm  
height of protective box, internal dimension: 100 mm

##### SK30/18-Q

shape of protective box: square  
thickness of protective box: 18 mm  
length of protective box, external dimension: 381 mm  
length of protective box, internal dimension: 306 mm  
width of protective box, external dimension: 385 mm  
width of protective box, internal dimension: 306 mm  
height of protective box, external dimension: 300 mm  
height of protective box, internal dimension: 282 mm

##### SK30/25-Q

shape of protective box: square  
thickness of protective box: 25 mm  
length of protective box, external dimension: 381 mm  
length of protective box, internal dimension: 292 mm  
width of protective box, external dimension: 385 mm  
width of protective box, internal dimension: 292 mm



---

height of protective box, external dimension: 300 mm  
height of protective box, internal dimension: 275 mm