



T30-1 Typ I-HRT

Fire protection door

Wood framed door leaf, approx. 68 mm single door leaf with fire protection T30 (Smoke control, sound insulation, burglary resistance, moisture resistance on demand).

- Je nach Einsatzgebiet, Ausführung und Größe kann die Leistung variieren
- Sonderlösungen projektbezogen möglich



Dimensions

Dimensions

Width (B)	500 - 1500 mm
Height (H)	1750 - 3000 mm
Height incl. Top panel	4000 mm
Door leaf thickness	approx. 68 mm

Technical details

Technical Details

Climate Class	DIN EN 12219	2
mechanical stress		group E
Installation options		Drywall Lindner partition systems Solid walls
Edge design (door leaf)		Solid wood inset edge band Solid wood edge band
Frame type		Wooden block frame Solid wooden frame Wooden enclosing frame Steel frame (one and two-piece)
Glazing		Frame width 135mm



Number of leaves		single-leaf
Standard equipment		Mortise lock, Class 3, prepared for profile and round cylinders Barrel door hinge 160mm with VX absorption Door closer superimposed or integrated automatisch absenkbar Bodendichtung (nur bei Rauchschutzausführung)
Additional equipment		Fitting combinations for emergency exit doors and panic bolts Monitoring contacts Access control Covered hinges
Door leaf weight		44 kg/m ²

Acoustics

Building acoustics

Weighted sound reduction index	ISO 717-1	R _w	43 dB
--------------------------------	-----------	----------------	-------

Fire protection

Fire resistance

Fire resistance	DIN 4102 5	92592
-----------------	------------	-------

Smoke Tightness

Smoke Protection	DIN 18095	RS
------------------	-----------	----

Safety

Security

Burglar Protection	DINV ENV 1627	WK2, WK3
Burglary protection	DIN EN 1627	RC1, RC2

Durability

Durability

Suitability for wet rooms	moisture resistant
---------------------------	--------------------




Surfaces

Surfaces

Surfaces	Real wood veneer HPL-Schichtstoff Lackiert Bauseitiger Anstrich/Grundierfolie
----------	--



Sustainability

Declarations	
Sustainable forestry	Our products can be supplied PEFC-certified (chain of custody certification). Certificate registration no.: TUEV-PEFC-COC-240109
Sustainable forestry	Our products can be supplied FSC™ MIX-certified (chain of custody certification) and fulfil all the necessary requirements. Zertifikatsnummer: TUEV-COC-000515-003
Sustainable forestry	Our products can be supplied FSC™ -certified (chain of custody certification) and fulfil all the necessary requirements. Certificate number: TUEV-COC-000515 Licence number: FSC-C119815
Evidence	
Green Level Certificate	<div>Basic   </div>