



COMPlacq

Aluminium lightweight panel

COMPlacq are non-combustible, lacquered aluminium lightweight panels. They are designed as system-independent, decorative ceiling and wall claddings.

The product version COMPlacq acoustic with a microperforated surface also contributes to effective room acoustic regulation. Thanks to their low weight, high rigidity and minimal deflection, these elements are perfect for large-format applications.

- stable aluminium sandwich panel
- available in RAL-color shades and other common color systems
- soundabsorbing due to micro-perforation
- low weight per unit area ca. 5.5 kg/m²
- non combustible
- easy to install and clean
- system independent
- IMO-certified

Examples for areas of application

Work: Common Rooms, Facilities for Meetings, Conventions and Conferences, Stage and Studio Rooms, Broadcasting Rooms, Television Studios, Utility Rooms, Assembly Rooms, Administration Buildings, Common Rooms, Facilities for Meetings, Conventions and Conferences, Office buildings, Data Centres and IT facilities, Assembly Rooms

Education: Research Rooms, Teaching, Class and Educational Rooms, Library, Higher education institutions and universities, Schools, Teaching, Class and Educational Rooms

Businesses, Recreation and Culture: Sales Areas, Places of Assembly, Banks, Shopping Centres, Cinema and multiplex cinemas, Concert Halls, Theatres and Opera Houses, Museums and Exhibitions, Sports Halls and Gymnasiums, Stadiums and arenas, Sales Areas, Places of Assembly

Healthcare: Pharmacies (Production), Laboratories and Research Facilities, Operating Theatres, Clean rooms (pharmacy and medical technology), Pharmacies (Production), Clinics and Hospitals

Hotels and Gastronomy: Commercial Kitchens, Hotels and Resorts

Public Institutions

Ship Fit-out

Residential building

Industry: Factories and production facilities

Transport: Airports

Public Areas: Escape Routes, Entrance Areas



Technical details

Technical Details

Climate area

12 - 30 °C



Dimensions

Dimensions

Panel thickness	14 mm
Panel weight	5.50 kg/m ²
Length (L)	2550 mm
Width (B)	1200 mm

Acoustics

Room acoustics

Sound absorber class	ISO 11654		B
Evaluated Sound Absorption Coeff.	ISO 11654	α_w	0.85

Fire protection

Building material class

Building material class		of the composite panel
Building material class	EN 13501-1	A2 - s1,d0
Designation by building authorities	EN 13501-1	non-combustible

Surfaces

Surfaces

Surfaces	Lackiert
Perforations	Rd 0,4-3 Rg 0,7-4

Sustainability


Declarations

Emission report	An expert opinion is available for the product with regard to its emission values. The test laboratory is accredited according to ISO 17025 and notified for EN 16516.
French VOC Regulation	Emission class A
Product Self-Declaration	A self-declaration in accordance with ISO 14021 is available. This contains extensive environmental information for planning, tenders and building certifications (LEED, DGNB, EU taxonomy).

Key figures

Recycled content	75 % 60 %
Building material class	Aluminiumplatte Aluminiumwabe
Indoor air measurement EN 16516	220 µg/m ³



Formaldehyde emissions	< 3 µg/m³
Evidence	
Indoor Air Comfort	Accomplished
AgBB	Accomplished
BREEAM International	Conform
LEED v4	Conform
DGNB	Conform
Green Level Certificate	<div>High </div> <p>Circularity: All components can be reused/ refurbished</p> <p>Life Cycle Assessment: Life Cycle Assessment according to DIN 14067 (Product Carbon Footprint) on request</p> <p>Cradle to Cradle Certified®: no C2C Certified® label available</p>

Combinable Systems

Combinable Systems	
Partitions	FIREwood - Composite wall cladding
Doors	T30-1 Type H T30-1 Typ I T30-2 Typ L T30-2 Typ M-HRT T30-2 Typ M T30-1 Typ I-HRT
Dry lining	Fireshield - Inspection door I 90 for service shafts

Applications

