Raw targets

3-layer element

Als Rohdiele versteht sich ein Vorprodukt zur Herstellung eines Parkettbelages nach DIN EN 13489. Die Fertigungstiefe kann nach Wunsch gewählt werden. Die niedrigste Fertigungstiefe stellt ein 3-Schicht verleimten Rohling nach Abmessung auf Kundenwunsch dar. Der Rohling ist für die Proflierung an einer Längsseite scharf geschnitten.

Folgende Optionen sind wählbar:

Fehlstellen mit 2K Polyesterpachtel verfüllt (Kittfarbe nach Kundenwunsch)
Astlöcher mit Fremdästen ausgebessert
Oberfläche geschliffen
Produkt-Vorteile:

Produktionstiefe frei wählbar
Fertig verleimter Rohling
Kundenorientierte Ausführungsvarianten

- Production depth freely selectable
- Ready glued blank
- Customer-orientated design variants

Dimensions

Dimensions	
Panel thickness	14 - 21 mm

Rev. 26.1
Lindner SE | Floors
Bahnhofstraße 29 | 94424 Arnstorf | Germany
Phone +49 8723 20-3682
E-Mail Floorsystems@Lindner-Group.com | www.Lindner-Group.com

We reserve the right to adapt and amend all details and information at any time. We do not accept liability for information that is inadvertently incorrect. Dimensional tolerances are permissible in compliance with the applicable standards. This document is protected by copyright law. Processing, unauthorised use or reproduction and public distribution are not permitted. Reproduction and distribution to third parties are only permitted with our express consent.