



## Alpine plank

### 3-layer 1-strip plank with tongue and groove system

Die Landhaus Diele Typ Alm als 3-Schicht Parkett verleimt, lebt von der Charakteristik und den Holzmerkmalen der Eiche. Durch den symmetrischen Aufbau wird bei kurzzeitig ungünstigen klimatischen Verhältnissen ein Querverzug verhindert. Mit dem Umlaufenden Nut-/Federsystem ist die Diele zur vollflächigen Verklebung auf normgerechten Untergründen geeignet. Der 3-lagige Aufbau reduziert das natürliche Quellen und Schwinden auf ein Minimum. Die Nuttschichtstärke von 4 mm ermöglicht eine Renovierbarkeit, ähnlich einem Massivparkett.

- Ressource saving thanks to quickly renewable raw materials
- Slim parquet build-up
- Client-orientated design variants
- Suitable for underfloor heating
- Initial care on site is recommended



#### Examples for areas of application

**Public Areas:** Entrance Areas, Escape Routes

**Work:** Common Rooms, Facilities for Meetings, Conventions and Conferences, Stage and Studio Rooms, Office Buildings, Assembly Rooms

**Film and Recording Studios**

**Education:** Libraries, Research Rooms, Universities and Higher Education Buildings, Schools

**Businesses, Recreation and Culture:** Banks, Museums and Galleries, Sports Halls and Gymnasiums, Places of Assembly

**Hotels and Gastronomy:** Restaurants and Catering Facilities, Hotels and Resorts

**Public Institutions:** Courts and Correctional Facilities, Town Halls, Government and Administrative Buildings

#### Technical details

---

##### Technical data

- **Wear layer thickness:** 4.0 mm
- **Thickness:** 14.0 mm
- **Length:** 2,000 mm, 2,200 mm, 2,400 mm
- **Width:** 160 mm, 190 mm, 210 mm
- **Build-up:** symmetric 3-layer structure
- **Profiling:** Tongue and grooving system with surrounding chamfer
- **Carrier layer:** Spruce - 2-layer cross glued
- **Thermal resistance:** 0.12 m<sup>2</sup> K/W
- **Building class:** D<sub>fl</sub>-s1
- **Emission class:** E1

##### Surface oiled A/B

- **Build-up:** 2-times hard wax oiled
- **Gloss level:** matt
- **Slip resistance class:** R9
- **Types of wood:** oak, smoked oak
- **Wood grading:** A/B - calm wood appearance, sporadic branches up to 20 mm

##### Surface oiled B/R

- **Build-up:** 2-times hard wax oiled



- Gloss level: matt
- Slip resistance class: R9
- Types of wood: oak, smoked oak
- Wood grading: B/R - rustic wood appearance, branches up to max. 60 mm, cracks

## Variants

### Design

Filler colour light brown



Filler colour dark brown



Filler colour black

