



Chalet plank

3-layer 1-strip plank in large format with tongue and groove system

Die Landhaus Diele Typ Chalet, als 3-Schicht Parkett verleimt, findet aufgrund ihrer stattlichen Abmessung Verwendung im gehobenen Innenausbau. Der hochwertige Gegenzug aus Eiche ermöglicht einen stabilen Aufbau bei großen Dielenbreiten. Durch den symmetrischen Aufbau mit Nutzschicht und Gegenzug aus gleichwertigem Holz wird bei kurzzeitig ungünstigen klimatischen Verhältnissen ein Querverzug verhindert. Mit dem Umlaufenden Nut-/Federsystem ist die Diele zur vollflächigen Verklebung auf normgerechten Untergründen geeignet.

Durch die höhere Rohdichte der Eiche gegenüber üblichen Nadelholzunterkonstruktionen wird ein niedriger Wärmedurchlasswiderstand erreicht, wie er für den Einsatz auf beheizten Estrichen erwünscht ist. Die Nutzschichtstärke von 4 mm ermöglicht eine Renovierbarkeit, ähnlich einem Massivparkett.

- impressive dimensions in length and width
- premium plank for a representative installation
- customer-oriented design variants
- product manufactured in-house



Examples for areas of application

Public Areas: Entrance Areas, Escape Routes

Work: Common Rooms, Facilities for Meetings, Conventions and Conferences, Stage and Studio Rooms, Office buildings, Assembly Rooms

Film- and Recording Studios

Education: Library, Research Rooms, Higher education institutions and universities, Schools

Businesses, Recreation and Culture: Banks, Museums and Exhibitions, Sports Halls and Gymnasiums, Places of Assembly

Hotels and Gastronomy: Gastronomy, Hotels and Resorts

Public Institutions: Courts and prisons, Government and municipal buildings

Technical details

Technical data

- **Layer thickness:** 4,0 mm
- **Thickness:** 17,0 mm
- **Length:** 2.600 mm, 2.800 mm, 3.000 mm
- **Width:** 240 mm, 270 mm, 300 mm
- **Fire behaviour:** Dfl-s1
- **Thermal resistance:** 0,13 m² K/W
- **Emission class:** E1

Surface oiled A/B

- Double hard wax oiled
- **Gloss level:** matt
- **Slip resistance class:** R9
- **Types of wood:** oak, smoked oak
- **Wood grading:** A/B - calm wood grain, isolated knots up to 20 mm

Surface oiled B/R

- Double hard wax oiled
- **Gloss level:** matt



- Slip resistance class: R9
- Types of wood: oak, smoked oak
- Wood grading: B/R - rustic wood grain, knots up to max. 60 mm, cracks