

Gallery board

3-layer boarded parquet for the combination with WOODline

3-layer boarded parquet elements for holohedral bonding on conventional screed or dry screed systems. The panel parquet elements with surrounding grooving are installed by means of an external tongue. The designs and the format of the panel parquet elements are based on the raised floors WOODline. With the same look, it is possible to combine conventional screed areas with raised floor.

- Panel parquet from our own production with highest quality
- Combination possibilities with our raised access floors
- Certified according to FSC™ possible
- Suitable for underfloor heating
- Further types of wood and designs upon request



Technical details

Wear layer thickness		4.0 mm
Thickness		16.0 mm
Length		600 mm
Width		600 mm
Build-up		symmetrical construction, 3-layer
Thermal resistance	EN 14342:2013	0.11 m ² K/W

Sustainability

Emission class	EN 717-1	E1
----------------	----------	----

Fire resistance

Building class	CWFT according to EN 14342:2013	D _{fl} -s1
----------------	---------------------------------	---------------------

Surface

lacquered	
Build-up	6-layer UV curing lacquer
Variants	lacquered colourless
Gloss level	matt
Slip resistance class	R9
Durability	Class 6
Types of wood	Oak, Oak smoked, Ash Eco, Bamboo light, Bamboo steamed
Wood grading	We use a wood grading with typical structure and play of colours, partly containing small sound knots
oiled	
Build-up	two times hard wax oiled
Variants	oiled colourless
Gloss level	matt
Slip resistance class	R9
Types of wood	Oak, Oak smoked, Ash Eco, Bamboo light, Bamboo steamed
Wood grading	We use a wood grading with typical structure and play of colours, partly containing small sound knots

Designs

Large baton 4	Large baton 6	Large baton 8	Large baton 9
			
3-strip 9	Large baton	Cube 81	Mosaic 4
			
Mosaic 9	Mosaic 16	Industrial 4-14 (Ash)	Industrial 4-18 (Ash)
			
Wide lamella (Bamboo)	Fine line (Bamboo)	Industrial 3-18 (Bamboo)	
			