

Prefabricated parquet plank

3-layer parquet

3-layer prefabricated parquet plank with tongue and grooving system for full-surface bonding on conventional screed or dry screed systems. The strip design of the board is based on the industrial designs of the raised access floor coverings. With the same look, it is possible to combine conventional screed surfaces with raised floor.

- Parquet layers from our own production with highest quality
- Combination possibilities with our raised access floors
- Real wood layer



Technical details

Thickness		approx. 15 mm
Length		1200 mm
Width		150/200 m
Fire behaviour		Di-s1
Thermal conductivity		0.13 W/(mK) – suitable for floor heating
Emission-tested		E1

Surface coating

Surface coating lacquered

Structure		7-layer UV curing lacquer
Variations		lacquered colourless lacquered neutral (non-flammable) lacquered coloured (white, grey, brown)
Gloss level		matt
Slip resistance		R10
Durability	I	Suitable for object use





Surface coating oiled

Structure		2-layer oil coated
Variations		oiled colourless
Slip resistance		R10
Gloss level		Silk-matt
Care instruction		Initial care treatment on site necessary

Standard program types of wood

Types of wood		Oak, smoked oak, walnut Further types of wood on request
Wood grading		We use a wood grading with typical structure and play of colours, partly containing small firmly integrown branches

Standard proram design

Industrial 3-18	Industrial 3-14	Industrial 3-10
		
Industrial 4-10		
		

Further designs on request.