



Direct suspended luminaire, equipped with LED technology. Option: with indirect light.

Housing made of sheet steel, powder-coated acc. to RAL colour card.

Light is distributed via a special microcell louvre cover, Suitable for office workplaces (UGR<19).

The luminaire can be additionally produced in different lengths or light strips according to project requirements.

Light unit: each 6 cells, length 281 mm, approx. 900 lumens output.

Delivery inclusive suspension set.

Type	Lumen	System Power	approx. Dimension (l x w x h)
QZP 600 1.5	1.800 Lumen	13 Watt	565 x 53 x 65 mm
QZP 900 2.5	2.700 Lumen	19 Watt	846 x 53 x 65 mm
QZP 1200 3.5	3.600 Lumen	26 Watt	1.127 x 53 x 65 mm
QZP 1500 4.5	4.500 Lumen	32 Watt	1.408 x 53 x 65 mm

Technical Data:

Voltage:	220-240 V / 50-60 Hz
Protection class:	1
Protection kind:	IP20
Ballast:	switchable
Cover:	cell louvre, white
Colour:	acc. to RAL
Light colour:	4.000K
Colour rendering:	RA>80

Options:

Light colour 3.000K
 Ballast DALI dimmable
 Direct / indirect light

Dimension drawing:

