



Direct suspended luminaire, equipped with LED technology. Option: with indirect light.

Housing made of Aluminium, powder-coated acc. to RAL colour card.

Light is distributed via a special microcell louvre cover, Suitable for office workplaces (UGR<19). Available in white, black, chrome and chrome matted.

The luminaire can be additionally produced in different lengths or light strips according to project requirements.

Light unit: each 7 cells, length 280 mm, approx. 1300 Lumens.

Delivery inclusive suspension set.

Type	Lumen	System Power	Dimension (l x w x h)
QZLP 600 2.5	2.600 Lumen	18,2 Watt	565 x 45 x 65 mm
QZLP 900 3.5	3.900 Lumen	27,3 Watt	845 x 45 x 65 mm
QZLP 1200 5.0	5.200 Lumen	36,4 Watt	1.125 x 45 x 65 mm
QZLP 1500 6.5	6.500 Lumen	45,5 Watt	1.405 x 45 x 65 mm

Technical Data:

Voltage: 220-240 V / 50-60 Hz
 Protection class: 1
 Protection kind: IP20
 Ballast: switchable
 Cover: cell louvre, standard white
 Colour: acc. ro RAL
 Light colour: 4.000K
 Colour rendering: RA>80

Options::

Light colour 3.000K
 Ballast DALI dimmable
 Direct / Indirect light
 cell louvre colours: black, chrome, chrome matted

Dimension drawing:

