



### Areas of application

- Office and conference rooms
- Industrial and factory areas
- Training and research facilities

### Construction options

- Single glazing

### Combinable systems

- Lindner Plus Acoustic Metal / Textile
- Doors for partition systems

### Description

The continuous fully glazed partition Lindner Life Nature ensures an open and transparent sense of space. This is complemented by a warm natural material with profiles made of oak. The construction of the system enables a assembly directly on site and allows a flexible adjustment to the spatial conditions.

	<b>Dimensions</b> (depending on material used)	
	Module width	Standard up to 1250 mm
	Height	Standard up to 3000 mm depending on glass thickness
	<b>Please note:</b>	<b>The maximum wall height and the maximum module width can differ depending on the building physics!</b>
	Wall thickness	55 mm
	Joint width	ca. 3 mm
	Glass pane thickness	10 / 12 / 16 mm safety glass
	<b>Technical data</b>	
	Weight	approx. 26 - 40 kg / m <sup>2</sup>
	Tolerances	± 10 mm in height and width resp. according to project-related planning
	<b>Sound insulation</b>	
	ISO 717-1	up to 40 dB Rw (=laboratory value)
	<b>Guidelines</b>	
	Product characteristic	Lindner visual assessment criteria for glazing systems

### Build connections

- **Joint seals:**  
the vertical joints are made with transparent tape or silicon
- **Connections:**  
connections with wooden profile or silicon

### Substructure

- wooden profiles

### Applicable standards

- DIN 4103
- ISO 717-1

### Surface finish glass

- Foils
- Screen printing
- Enamel

Subject to change without notice. This document is our intellectual property. It may neither be duplicated, exploited for profit, distributed for business purposes nor shown to any third parties without our approval.

Customised, project-specific solutions possible

Further information can be found on our homepage [www.Lindner-Group.com](http://www.Lindner-Group.com)

