🕻 Lindner



Thickness of the door leaf

Weight of the door leaf

Standard equipment

Access control

Barrel door hinge 100mm with VX absorption

Glass door lock; class 3; prepared for PZ

prepared for profile and round cylinders Automatically lowerable bottom seal

etc. according to the demands and customer requests

On both sides offset door handle

Additional equipment / options Superimposed door closer

Sound insulation ISO 717-1

Product data sheet Sound insulation door GTB 13

Dimensions

Door leaf width (1 door leaf) Door leaf height 500 mm up to 1125 mm up to 2375 mm

System description

All-glass door leaf made of VSG laminated safety glass out of semitempered glass (TVG) 12 mm; clear glass; edge quality according to DIN EN 1249-11: KPO and KGS polished and arrised edges; available as single leaf

Installation options

Solid wall Plasterboard partitions Lindner partition systems

13 mm

approx. 34 - 37 kg/m²

• single leaf up to 37 dB Rw

(= laboratory value)

Glass design

- Clear glass
- Low iron glass

Door frame

- aluminium door frame
- steel door frame (one- or two-piece)
- Wooden door frame

Information on Lindner Group



and its related logo, is a trendmark owned by the U.S. Green Building Council ®

Further information can be found on our

Specific solutions are project-related possible

standard

0

optional possible homepage www.Lindner-Group.com

