



Areas of application

- Office and conference rooms
- Industrial and factory areas
- Training and research facilities

Construction options




- Fastened to the wall
- Free standing

Combinable systems

- Lindner Life Stereo 125
- Lindner Life Contour 126
- Lindner Life Freeze 137
- Lindner Logic 100 Metal / Timber
- Lindner Logic 100 Metal / Timber - Acoustic
- Lindner Plus Accessories

Description

Our wall cladding system Lindner Free Timber creates a comfortable feel and comes in a wide variety of surfaces. The versatile substructure enables spacesaving and ease of assembly.

	Dimensions (depending on material used)	
	Module width	300 - 1500 mm
	Height	<ul style="list-style-type: none"> • Standard up to 5000 mm (free-standing) • undivided up to 3000 mm (free-standing) • unlimited (attached to load-bearing walls)
	Joint width	6 mm (optional 8 mm)
	Overall width	about 60 mm
	Technical data	
	Weight	approx. 17 - 27 kg / m ²
	Green Building	
	Product characteristic	DGNB- / LEED- compliant

Build connections

- **Connection accessories:** depending on the system stud used, hidden hooks are installed into the vertical shadow gaps at modular centres
- **Joint seals:** seals/sealing tapes are installed on the floor, ceiling and support profiles
- **Connections:** relocatable floor, ceiling and wall connections
- All partition systems are combinable with our system wall absorber

Advantages at a glance

- Performance in different substructures
- Arbitrary joints, even with round performance
- Special surfaces such as foils or even antibacterial

Substructure

- Steel studs, constructed from folded or rolled steel sheet profiles, zinc coated or laquered

Information on Lindner Group



and its related logo, is a trademark owned by the U.S. Green Building Council ©

Customised, project-specific solutions possible

Further information can be found on our homepage www.Lindner-Group.com

